



NexxaCore Technical Datasheet – The District & The Peaks Collection

Plank Size & Packing	7" x 48" (The District) 28.36 sf/box, 12 pc/box, 40 lbs/box 50 bxs/pallet; 2050 lbs/pallet		
	9" x 60" (The Peaks) 29.92 sf/box, 8 pcs/box, 48 lbs/box 56 bxs/pallet, 2750 lbs/pallet		
Overall Thickness	8mm		
Bevel & Texture	Accented Bevels™ w/ EIR Technology		
Wear Layer	Guardia 20™ –20 Mil commercial urethane wearlayer with aluminum oxide (0.5mm)		
Vinyl Layer	1.5mm virgin PVC with WoodVision™ HD film		
Core	5mm Nexxacore™ with zero wood fibers		
Underlayment	1.5mm Silencio XPE™ closed cell, acoustical underlayment		
Locking System	Unilin Uniclic 2G		
Installation	Floating		
Warranty	Lifetime Limited Residential Wear Warranty Lifetime Limited Structural Warranty Lifetime Limited Waterproof Warranty 10 Year Limited Medium Commercial Warranty		
Compliance	CA Carb Compliant Floorscore Certified		
Test Data	Static Load	ASTM F-970	Pass
	Dimensional stability	ASTM F2199	Pass
	Fire Rating	ASTM E648	Class 1
	IIC	ASTM E492	72dB
	STC	ASTM E90	73Db
	Slip resistance	ASTM C1028	Pass
	Phthalates	EN14372	Not Detectable