



NexxaCore Technical Datasheet – The Lands Collection

Plank Size & Packing	7" x 48" 23.68 sf/box, 10 pc/bx, 40 lbs/box 50 bxs/pallet; 2050 lbs/pallet		
Overall Thickness	5mm		
Bevel & Texture	Accented Bevels™ w/ standard texturing		
Wear Layer	Guardia 12™ –12 Mil light commercial urethane wearlayer with aluminum oxide (0.5mm)		
Vinyl Layer	none		
Core	4mm extruded Rigid Nexxacore™		
Underlayment	1.0mm Silencio XPE™ closed cell, acoustical underlayment		
Locking System	Unilin Uniclic 2G		
Installation	Floating		
Warranty	Lifetime Limited Residential Wear Warranty Lifetime Limited Structural Warranty Lifetime Limited Waterproof Warranty 5 Year Limited Light Commercial Warranty		
Compliance	CA Carb Compliant Floorscore Certified		
Test Data	Static Load	ASTM F-970	Pass
	Dimensional stability	ASTM F2199	Pass
	Fire Rating	ASTM E648	Class 1
	IIC	ASTM E492	72dB
	STC	ASTM E90	73Db
	Slip resistance	ASTM C1028	Pass
	Phthalates	EN14372	Not Detectable